



# JHW130N-1 Protective Tape

High quality Soft PVC Film, coated with a strong rubber based adhesive, hand applicable.

## FEATURES:


- Rubber adhesive
- PVC carrier

## BENEFITS:

- Orange
- Highly conformable
- Meet RoHS & REACH

## STANDARD SIZES:

Length: 25m, 33m  
Width: 48mm, 50mm  
Core ID: 76.2mm



## COLORS:

Orange

Other sizes and colors are available on request.

## JHW130N-1

Properties	Value	Unit	Test Method
Total thickness	0.130±0.025	mm	EN 1942
Tensile strength	≥15	N/cm	ISO 29864
Elongation at break	≥150	%	ISO 29864
Adhesion strength			ISO 29862
— to steel	≥1.0	N/cm	
Tack	≥6	#	GB/T 4852

Note: The listed values are required only and not intended to serve as product specifications

### RECOMMENDED USES:

Used for general surface protection, particularly in construction equipment wrapped protection.

### STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



#### Avery Dennison Yongle Tape

No.9 East Yangji Road, Industrial Park,  
Zhuozhou, Hebei, P.R. China  
Post code: 072750

TEL: 0510-82021817 / 13921396678

For more information on our tapes and adhesive solutions, visit [www.yongletape.com.cn](http://www.yongletape.com.cn)